

Amendments To The Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-52 (Cancelled)

53. (Previously Presented) Vibration isolating pipe clip for securing a pipe to a support, in particular for securing a medium-carrying pipe to a wall or ceiling of a building, comprising:

- a rigid pipe clip body which is composed of one or more parts and is provided with securing means for securing the pipe clip body to a support,

- a vibration isolating member which bears against an inner circumference of the pipe clip body and is ultimately positioned between an outer circumference of the pipe and the pipe clip body,

wherein the vibration isolating member is a porous vulcanized rubber with closed cavities and separating walls between them,

wherein the cavities are substantially unpressurized by dehydration of salt which remains in the cavities, in such a manner that in the event of a reduction in the volume of the

cavities under the influence of deformation of the vibration isolating member, no significant pressure increase occurs inside the cavities,

wherein the vibration isolating member has a form factor defined by the quotient of the surface area which is subject to load and the free surface area, and in which the cavities significantly reduce the form factor, and

wherein the form factor of the vibration isolating member is less than 0.2.

54. (New) Vibration isolating pipe clip for securing a pipe to a support, in particular for securing a medium-carrying pipe to a wall or ceiling of a building, comprising:

- a rigid pipe clip body which is composed of one or more parts and is provided with securing means for securing the pipe clip body to a support,

- a vibration isolating member which bears against an inner circumference of the pipe clip body and is ultimately positioned between an outer circumference of the pipe and the pipe clip body,

wherein the vibration isolating member is a porous vulcanized rubber with closed substantially unpressurized

cavities and separating walls between them having a chemical from which water has been cleaved,

wherein the unpressurized cavities when reduced in volume by deformation of the vibration isolating member, produce no significant pressure increase inside the cavities.

55. (New) The vibration isolating pipe clip for securing a pipe to a support according to claim 54, wherein the chemical from which water has been cleaved is a salt.

56. (New) The vibration isolating pipe clip for securing a pipe to a support according to claim 55, wherein the vibration isolating member has a form factor defined by the quotient of the surface area which is subject to load and the free surface area, and in which the cavities significantly reduce the form fact.

57. (New) The vibration isolating pipe clip for securing a pipe to a support according to claim 56, wherein the form factor of the vibration isolating member is less than 0.2.

58. (New) The vibration isolating pipe clip for securing a pipe to a support, in particular for securing a medium-carrying pipe to a wall or ceiling of a building, comprising:

- a rigid pipe clip body which is composed of one or more parts and is provided with securing means for securing the pipe clip body to a support,

- a vibration isolating member which bears against an inner circumference of the pipe clip body and is ultimately positioned between an outer circumference of the pipe and the pipe clip body,

wherein the vibration isolating member is a porous vulcanized rubber with closed cavities and separating walls between them, and

wherein the cavities are substantially unpressurized by dehydration of salt which remains in the cavities, in such a manner that in the event of a reduction in the volume of the cavities under the influence of deformation of the vibration isolating member, no significant pressure increase occurs inside the cavities.